

# MT6LD

## SAFETY VALVE - LEAK DETECTOR

### SPECIFICATION SHEET



#### FEATURES:


- PROTECTS AGAINST WATER DAMAGE, EVEN IF NOBODY IS HOME
- AUTOMATICALLY SHUTS OFF WATER SUPPLY AND SOUNDS ALARM WHEN LEAK IS DETECTED
- USES 9V ALKALINE BATTERY (INCLUDED)
- QUICK CONNECT 1/4" ADAPTERS INCLUDED
- AUTOMATICALLY SOUNDS ALARM AND SHUTS OFF WATER IF BATTERY IS LOW
- ESTIMATED BATTERY LIFE: 2 YEARS




#### SPECIFICATIONS:

VOLTAGE	9V DC
CURRENT	1.0 mA TYPICAL, 15.0 mA MAX
CABLE LENGTH	60"
CONNECTORS	1/2" BSP (1/4" PUSH FIT ADAPTERS)
ENVIRONMENT TEMPERATURE	33 - 176 °F
MAX PRESSURE	87 PSI
VALVE BODY MATERIAL	POM (POLYOXYMETHYLENE)
VALVE MECHANISM	SOLENOID
MAXIMUM FLOW RATE	2.0 GALLONS/MIN AT 50 PSI

#### INCLUDED COMPONENTS:



LEAK DETECTOR




SHUT-OFF VALVE



BATTERY



36" OF 1/4" TUBE



TEE



1/4" PUSH FIT ADAPTER (x2)



7/16" UNS FEMALE ADAPTER



9/16" UNEF FEMALE ADAPTER



9/16" UNEF MALE ADAPTER

#### WARRANTY

FOR WARRANTY INFO PLEASE VISIT [WWW.MOUNTAINPLUMBING.COM/PAGE/RESOURCES/WARRANTY](http://WWW.MOUNTAINPLUMBING.COM/PAGE/RESOURCES/WARRANTY)

#### FINISH CARE & MAINTENANCE

NEVER USE ANY HARSH ALKALI, ACID BASED DETERGENTS OR CLEANERS SUCH AS SOFT SCRUB®, SCRUBBING BUBBLES® OR COMET® TO CLEAN. DO NOT USE BRILLO® OR SCOTCH BRITE® PADS. THESE WILL ALL HARM THE FINISH. TO CLEAN, USE ONLY A DAMP SOFT CLOTH AND WIPE GENTLY. STANDARD WINDEX® CAN ALSO BE USED SPARINGLY. IT IS NOT NECESSARY TO WIPE HARD TO REMOVE SPOTS. TO MAINTAIN THE FINISH, WIPE WITH A SOFT DRY CLOTH AFTER USE. AN OCCASIONAL COAT OF PURE CARNAUBA WAX WITHOUT CLEANERS WILL HELP PROTECT THE FINISH.

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE